

THE MOST COMPACT PORTABLE STRAPPING TOOL

ZAPAK

100Kgs.
TENSION



FEATURES

- Reliable manual tensioning, Max. 100kgs, for light duty strapping job.
- Automatic friction-weld sealing and cutting, no metal seals required.
- Sturdiest Dupont Nylon plus fiber glass plastic case.
- Lightweight and compact size for easy operation and store-away.
- Adjustable sealing time for various strap specifications.
- Built-in safety switch ensures straps to be positioned for operation.
- User self-adjustable strap width guiders to fit different widths of straps.
- User self-changeable cutting blade to save maintenance cost & time.
- Modularized mechanism provides easy and low cost maintenance.
- Easy “One-Step” straps inserting.
- Perfect for office, small working sites and commercial goods.

SPECIFICATION

Model	Voltage A/C	Frequency	Fits Poly- strap	Width		Thickness		Tension Range Kgs.	Sealing Efficiency	Dimension
				mm	inch	mm	inch			
ZP2010	100V	50/60Hz	PP	9-16	3/8-5/8	0.55-1.0	.022-.04	20-100	80+-5%	9 7/8" x 4 3/16" x 5 1/2" weight: 2.73Kgs (6.0Lbs.)
ZP2011	120V+-10V									
ZP2012	230V+-10V									

- Max. tension performance varies based on different strap specifications and quality.
- Sealing efficiency varies based on strap quality and set sealing time.
- Equipped with 11mm, 12mm, 13mm strap width adjustment guiders to fit different strap widths.

YOUR DISTRIBUTOR



©2010 Pantech International Inc. All rights reserved.

Worldwide Patented.

Printed in Taiwan, R.O.C.

ZAPAK is a registered trademark of Pantech International Inc.

Product and specifications subject to change without notice.

One Year limited manufacturer warranty